



## XR 212-32

### Refrigeration Lubricant

#### Product Description

XR 212-32 is a high performance refrigeration compressor lubricant based on a premium naphthenic mineral oil. The excellent stability and low temperature properties make this product ideal for a wide variety of refrigeration applications. XR 212-32 is wax free which prevents solid formation in the evaporator and expansion valve.

#### Applications\*

- R-22
- R-123
- R 414A

\* To assure proper lubricant selection, please consult your Xaerus Performance Fluids representative

#### Health and Safety

Based on available information, XR 212-32 is a non-toxic, non-hazardous product that is not expected to cause any adverse health effects when used as designed. Users are advised to follow the recommendations provided in the MSDS.

## Typical Properties

Criteria	Value	Method
Viscosity, cSt @ 40° C	32.0	ASTM D-445
Viscosity, cSt @ 100°C	4.7	ASTM D-445
Viscosity Index	31	ASTM D2270
Flash Point, °F/°C	358/181	ASTM D-92
Pour Point, °F/°C	-40/-40	ASTM D-5950
Moisture, ppm	20	ASTM D-6304
Specific Gravity @ 77°F/25° C	0.904	ASTM D-4052
Density, lb/gal	7.53	ASTM D-4052
Color	0.5	ASTM D-1500
Aniline Point, °F/°C	183/84	ASTM D611

Notice: The information and statements above are based on information we believe to be reliable; however, we expressly do not represent, warrant or guarantee the accuracy, completeness, or reliability of the same.